

Feeder Pillar

Topaz's Feeder Pillar is designed and manufactured to customer requirements and meet international standards. Our products are designed and fabricated with high quality and safety in mind for various industries applications.

Features:

- Phase and neutral busbar
- Earth busbar
- Incoming termination link
- Support insulator
- Steel cable clamp
- Disconnecting link
- Outgoing termination link

Specifications:

Rated current	: 400A – 2 nos. incoming, 160A – 6 nos. outgoing
Rated Voltage	: 440 VAC
Rated insulation voltage	: 1000 V
Rated short circuit withstand	: 6kA/1s
Cable termination	: 300 sq mm (incoming), 70 sq mm (outgoing)
Fuse base	: 160A (suitable for DIN fuses) for NH Fuse 100A
Zone Location	: Safe Zone, Indoor or Outdoor
Enclosure material	: Mild Steel
Color	: Grey
Ingress Protection	: IP54
Standards	: IEC 60439-1, 60529
Approval	: Energy Commission (Suruhanjaya Tenaga), JKR



For additional information please contact;

Topaz Integrated Technology Sdn. Bhd.

46, Jalan Saujana 2, Taman Industri Saujana

09600 Lunas, Kedah, MALAYSIA

Tel: +604-484 7252 Fax: +604-484 9646

E-mail: sales@topazit.com Web: www.topazit.com

